CLINVERTEC PRO

Clinvertec PRO allows you to **automate all the control of the climatic elements of your crop** such as windows, shading/thermal screen, fans, air extractors, cooling, etc., in order to make decisions automatically and independently depending on the reception of data and programmed parameters **(temperature, humidity, solar radiation, etc.).**

Maximum control of climatic variables inside the greenhouse.

Adapted to any type of **crop and climate**.

Automation and programming of all climatic elements in an easy and intuitive way.

Maximum productivity in your crops obtaining maximum profitability.

Easy operation and remote control through the APP for Android and iOS.

CLINVERTEC PRO is designed for the control of climatic variables in protected environment crops.

Thanks to its modular system, it allows you to design the perfect combination adapted to the needs of your project or crop.



CLINVERTEC PRO 7C	CLINVERTEC PRO 10C	CLINVERTEC PRO 10
		

Number of climatic zones	1 - 2 Climatic Zones	1 - 4 Climatic Zones	1 - 12 Climatic Zones
Dimensions (L-W-H)	43 x 20 x 53 cm	43 x 25 x 65 cm 54 x 31 x 75 cm	70 x 54 x 112 cm
Approximate weight	20 kg	25 kg	50 kg
Adapted to any type of cultivation in a protected environment	●	●	●
Zenithal windows	2 Zenithal windows per zone	2 Zenithal windows per zone	2 Zenithal windows per zone
Perimeter Windows	1 Perimeter window per zone	4 Perimeter window per zone	4 Perimeter window per zone
Shading Screen	1 Shading screen per zone	1 Shading screen per zone	1 Shading screen per zone
Isolation screen / Blackout	1 Screen per zone*	1 Screen per zone*	1 Screen per zone

	CLINVERTEC PRO 7C	CLINVERTEC PRO 10C	CLINVERTEC PRO 10
Outdoor Screen	●	●	●
Air blowers	2 Air Blowers per zone*	2 Air Blowers per zone*	3 Air Blowers per zone
Humidification / Fogging	●	●	●
System of hot air heating	●*	●	●
Cooling	1 Signal per zone	1 Signal per zone	3 Signals per zone
Double plastic	1 Signal per zone	1 Signal per zone	1 Signal per zone
CO_2	1 Signal per zone*	1 Signal per zone*	1 Signal per zone
Assimilation lights	1 Signal per zone*	1 Signal per zone	1 Signal per zone
Compact weather station	●	●	●
Graphics and historical	●	●	●
Control from mobile, tablet or PC	Optional: PC and mobile remote control license	License included in the price	License included in the price
Multiple programming possibilities	●	●	●
Alarms and notifications	●	●	●
Structure stainless steel AISI 304	-	-	●
Polyester structure	●	●	-
Manual or automatic activation	●	●	●
7" Touch-screen display	●	-	-
10" Touch-screen display	-	●	●

(*)It is required to add an extension module.

Note: 230V supply voltage is considered.

Ritec Agrotechnology
Ctra. de Circunvalación, s/n.
P.O. Box 163
30880 Águilas, Murcia, España.

Contact us:
Phone: +34 968 446 000
E-mail: ventas@ritec.es
Web: www.ritec.es